

Dejero

WayPoint 204

High-quality four-output SMPTE ST 2110 receiver



The WayPoint 204 receiver reconstructs broadcast-quality video transported over multiple IP connections from Dejero transmitters, decodes HEVC or AVC, and outputs to SMPTE ST 2110 workflows.

WayPoint 204 has been engineered for broadcast-quality reliability, equipped with dual power supplies and redundant storage hard drives with RAID protection giving you peace of mind.

Decoding up to four simultaneous ingests in a single 1U device you gain flexibility and save valuable rack space in your facility.



CODEC AUTO-DETECTION

Compatible with any Dejero transmitter, WayPoint receivers auto-detect whether the incoming transmission is HEVC (H.265) or AVC (H.264) and decodes accordingly.



IFB & INTERCOM SUPPORT

Communicate with camera operators and talent in the field while in live and stand-by mode with one-way, balanced interruptible foldback (IFB) and two-way, full-duplex voice communication intercom feature.

*Additional hardware required



SAVE RACK SPACE

A single device receives and outputs transmissions from up to four different sources simultaneously—optimizing valuable rack space in your facility.



BUILT-IN REDUNDANCY

Engineered for reliability, WayPoint 204 uses industry-proven hot-swappable power supplies and front-access 1 TB hard drives with RAID protection for both power and storage redundancy.

PRODUCT SPECIFICATIONS

KEY FUNCTIONS

RECONSTRUCTS	Broadcast-quality video transported over multiple IP connections
DECODES	HEVC or AVC
OUTPUTS	4 x SMPTE 2110 IP streams, with redundancy (SMPTE ST-2022-7)

SMPTE ST 2110 OUTPUT

VIDEO	Formats: 1080i 25/29.97/30, 1080p 23.98/25/30/50/59.94/60
AUDIO	2-, 4-, or 8-channel for live transmission Note: Transmitters sending recorded clips will send 2- or 4-channels of audio.

VIDEO NETWORK CONNECTIONS 2-2 x 25 GbE SFP28

DATA NETWORK CONNECTIONS

ETHERNET 2 x 1 Gb/s port for LAN/WAN

POWER

SUPPLY	2 x 100-240 VAC 50/60 Hz AC
CONSUMPTION	Max. 400 W (redundant)

PHYSICAL

DIMENSIONS (H x W x D)	1U 19" rack-mount, 4.3 x 43.7 x 50.3 cm (1.7 x 17.2 x 19.8 inches)
WEIGHT	9.5 kg (20.8 lbs)
OPERATING TEMPERATURE	10 °C to 35 °C (50 °F to 95 °F)
STORAGE	300+ hours of HD (6 Mb/s)
INTERFACES	2 x SFP28 Ethernet, 2 x RJ45 Ethernet, 4 x IFB (1/4" TRS connectors), VGA (DB9)



SFP28 ETHERNET



IFB



RJ45 ETHERNET

ADDITIONAL FEATURES

4x OUTPUTS

Supports four outputs to SMPTE ST 2110 workflows

HIGH PERFORMANCE

Quad-core Intel Xeon processor designed for all day, every day reliability

FRONT ACCESS STORAGE

Two hot-swappable (front access) 1 TB hard drives with RAID protection

BACKWARDS COMPATIBILITY

Fully compatible with all non-HEVC Dejero transmitters

MULTICHANNEL AUDIO

Supports 2, 4, or 8 different simultaneous audio outputs

MANAGE ANYWHERE

Manage all your receivers and output assignments remotely from any device with a web browser

SOFTWARE UPDATES

New and enhanced features and compatibility with new devices is provided with software updates

Contact us to learn more about **WayPoint 204**

Full specifications available at www.dejero.com/waypoint

Dejero

www.dejero.com
connect@dejero.com
+1 519 772 4824

Copyright © 2020 Dejero Labs Inc. Dejero is a trademark or a registered trademark of Dejero Labs Inc. All other trademarks are the property of their respective owners. Design, features, and specifications are subject to change without notice. D-PB125-003 10/2020